

INSTALLATIONGUIDE

FIAT / Citroen / Peugeot

2.2 / 2.3 / 3.0



14105000

The product described in the guidance was developed, manufactured and controlled considering the necessary safety requirements.

The product must be installed properly to ensure a proper function and avoid danger for persons and things.

Please read this installationguide inclusive safety instructions carefully.

Scope of supply:

| Quantity | article |
|----------|---------------|
| 1x | Tuningbox |
| 1x | Loom |
| 1x | Bridge plug |
| 1x | Fastening kit |



- 1.Open the hood.
- 2.Turn the ignition off!
- 3.Remove the ignitionkey!
- 4.Close and lock all doors!
- 5.Do not open any doors while installing the tuningkit!
- 6.Wait 5 minutes before beginning the installation



In order to avoid damages at electronic vehicle components, you have to be sure that you have done all necessary methods for **electostatic discharge** .

Install the electronic in an **waterproof** and **vibrationless** place. Do not make any changes at the tuning-kit!

Do not expand or shorten the loom.

INSTALLATIONGUIDE


FIAT / Citroen / Peugeot

2.2 / 2.3 / 3.0



14105000

Overview



Overview:

The tuningkit has to be attached to the following points:

- boost pressure sensor
- Rail pressure sensor
- Cam shaft

Required tools:

- none


Preperation:

- Move the individual strands of the loom to the associated plug connectors
- Put the required tools by your side (if needed)
- Take the fastening material at your side

INSTALLATIONGUIDE

FIAT / Citroen / Peugeot

2.2 / 2.3 / 3.0



14105000

1



1. Preperation

- ◇ Before you can start installing the kit, you have to remove the engine cover.
- ◇ The engine cover is only clipped

2



2. Cam shaft sensor

- ◇ Disconnect the plug from the cam shaft sensor
- ◇ Attach the throttle body switch plug to the new loom
- ◇ Connect the plug of the new loom the cam shaft sensor

INSTALLATIONGUIDE


FIAT / Citroen / Peugeot

2.2 / 2.3 / 3.0



14105000

3



3. Rail pressure sensor

◇ The rail pressure sensor is located directly at the common rail on the driver-site beneath the air supply

4



- ◇ Disconnect the plug from the rail pressure sensor
- ◇ Attach the rail pressure plug to the new loom
- ◇ Connect the plug of the new loom the rail pressure sensor

INSTALLATIONGUIDE


FIAT / Citroen / Peugeot

2.2 / 2.3 / 3.0



14105000


5



4. Boost pressure sensor

◇ The boost pressure sensor is located beneath the common rail in the middle of the engine

6



- ◇ Disconnect the plug from the boost pressure sensor
- ◇ Attach the boost pressure plug to the new loom
- ◇ Connect the plug of the new loom the boost pressure sensor

INSTALLATIONGUIDE


FIAT / Citroen / Peugeot

2.2 / 2.3 / 3.0



14105000

7



5. Tuningbox

- ◇ Finally install the cable towards a suitable position
- ◇ The plugs must be engaged, so that a safe connection is ensured
- ◇ Fix the cable with cable ties
- ◇ Connect the tuningbox to the new loom