



Original BMW Accessories 17-inch BMW Performance brake system (FA only) with BMW Performance brake disc perforated and grooved

- E90* (318i, 320i, 323i, 325i, 328i, 318d, 320d)
- E92* (320i, 323i, 325i, 328i, 320d)

* Can only be fitted on 4-cylinder after 03/07, 6-cylinder after 06/06

Accessories

Management
Marketing
Sales of new Cars
Sales of used Cars
Aftersales
Administration

Product description

- 6-piston aluminium fixed calliper on the front axle painted in BMW "Performance yellow" including "BMW Performance" lettering in ferric grey.
- Perforated and grooved, internally ventilated brake discs on the front axle.
- Not available ex-works.

Sales features / benefits

- The 17-inch BMW Performance brake system improves the thermal load capacity because of larger, internally ventilated brake discs.
- The holes and grooves in BMW Performance brake discs reduce formation of a film of water between the brake pad and the brake disc.
- Lower weight, therefore less unsprung mass.
- More attractive look.
- Underlines the sporty character, particular when combined with alloy wheels with an open wheel design.

Homologation

From 09/2008 onwards, the BMW Performance brake system is included in EC homologation nos.
e1*2007/37*0308*09 (E90, E91)
e1*2007/37*0346*08 (E92, E93)

Nevertheless, national approval and amendment of the vehicle registration documents are always required since the brake system's data that is relevant for registration changes.

National approval must be obtained for cars built before 09/2008 with TÜV test report (no. 08-00047-CP-GBM-00).



Safety note

The DSC coding must be adapted to the BMW Performance brake. This is possible in cars with 4-cylinder engines after 03/07 and 6-cylinder engines after 06/06.

The BMW Performance brake is only approved for use in conjunction with at least 17-inch aluminium wheels (also in winter). ◀

Please ensure that you pass this information on to the customer.



BMW Performance brake system



Note

- No work is required on the rear axle. The standard brake system remains in the car. Installation must be as described in the special BMW Performance installation instructions.
 - The car must be carefully run in during the first 200 km after installation of the brake system, then the full effectiveness of the brake system is available.
 - As a result of the special construction of the perforated and grooved brake discs, they may generate noise when the brakes are used, but this has no effect on the stability of the brake discs.
- Sticker to show that the BMW Performance brake system is installed.

Availability
from 03/2008

Installation time
approx. 2.5 hours

EPC DVD
from 03/2008

Installation instructions
see BMW Aftersales Assistance Portal (ASAP)
01 29 0 444 739

Part number
17-inch BMW Performance
brake system kit 34 11 0 444 738

Please refer to your price system or the latest price publications for the latest prices.